



Yamaha V6 Offshore



Specifications	F300 OFFSHORE	F250 OFFSHORE	F225 OFFSHORE
Engine Type	V6 (60°)	V6 (60°)	V6 (60°)
Displacement	4.2L (254 ci)	4.2L (254 ci)	4.2L (254 ci)
W.O.T. RPM Range	5000-6000	5000-6000	5000-6000
Alternator Output @ W.O.T.	70A	70A	70A
Compression Ratio	10.3:1	10.3:1	10.3:1
Fuel/Induction System	DOHC Fuel Injection VCT	DOHC Fuel Injection VCT	DOHC Fuel Injection VCT
Lubrication	Wet Sump	Wet Sump	Wet Sump
Ignition System	TCI Micro Computer	TCI Micro Computer	TCI Micro Computer
Preferred Fuel Octane	89 P.O.N.	87 P.O.N.	87 P.O.N.
Starting System	Electric	Electric	Electric
Shaft Length	25 in, 30 in	25 in., 30 in.	25 in
Gear Ratio	21:12 (1.75)	21:12 (1.75)	21:12 (1.75)
C.A.R.B. Rating	3-Star	3-Star	3-Star
Weight*	562 lb (255 kg)	562 lb (255 kg)	562 lb (255 kg)
Warranty	3 Year Limited Pleasure Boat - 1 Year Limited Commercial	3 Year Limited Pleasure Boat - 1 Year Limited Commercial	3 Year Limited Pleasure Boat - 1 Year Limited Commercial

* Weight refers to shortest shaft length available.

** Consult your dealer for optional equipment.

Specifications subject to change without notice. Consult your dealer for optional equipment.

©2010 Yamaha Motor Corporation, U.S.A.